

Part number:

HYDROMA

HYDRAULICKÉ SYSTÉMY

HIDROMA
SYSTEMS

UKŁADY HYDRAULICZNE

HYDROMA

ГИДРАВЛИЧЕСКИЕ СИСТЕМЫ

Fixed displacement axial piston pumps and motors 310 series

TECHNICAL CATALOGUE

PSM-HYDRAULICS

2011



המלכה בת ה-14

Contents

Ordering Code.....4

Technical characteristics.6

Determination of pump nominal size.....7

Determination of motor nominal size.....7

Requirements for working fluids.7

210.12 Overall dimensions8

310.12 Overall dimensions12

310.2.28 Overall dimensions.....16

310.3(4).56 Overall dimensions.....20

310.3(4).112 Overall dimensions.....24

310.3(4).160 Overall dimensions.....26

310.3(4).250 Overall dimensions.....28

Ordering Code

A	B	C	D	E	F	G	H	I

● = standart program

o = optional

- = not available

A - series

code	description	12	28	56	80	112	160	250
310	310 series	●	●	●	●	●	●	●
210	210 series	●	-	-	-	-	-	-

B - product version

code	description	12 ¹⁾	28 ¹⁾	56	80	112	160	250
2	ball bearing, bronze cylinder block	●	●	● ²⁾	-	● ²⁾	-	-
3	tapered roller bearing, bronze cylinder block	-	-	●	●	●	●	●
4	tapered roller bearing, steel cylinder block	-	-	●	●	●	●	●

C - displacement

code	description	12	28	56	80	112	160	250
12	12 ccm/rev	●	-	-	-	-	-	-
28	28 ccm/rev	-	●	-	-	-	-	-
56	56 ccm/rev	-	-	●	-	-	-	-
80	80 ccm/rev	-	-	-	●	-	-	-
112	112 ccm/rev	-	-	-	-	●	-	-
160	160 ccm/rev	-	-	-	-	-	●	-
250	250 ccm/rev	-	-	-	-	-	-	●

D - mounting flange

code	description	12	28	56	80	112	160	250
0	ISO 3019/2, 4 hole	●	●	●	●	●	●	●

E - product type, rotation and shaft end

code	type	rotation	shaft end	12	28	56	80	112	160	250
0	motor	reverse	splined shaft GOST 6033-51	-	●	-	-	-	-	-
			splined shaft GOST 6033-80	●	-	●	●	●	●	●
1	motor	reverse	parallel keyed shaft	●	●	●	●	●	●	●
2	motor	reverse	gear end	-	-	●	-	-	-	-
3	pump	right	splined shaft GOST 6033-51	-	●	-	-	-	-	-
			splined shaft GOST 6033-80	●	-	●	●	●	●	●
4	pump	left	splined shaft GOST 6033-51	-	●	-	-	-	-	-
			splined shaft GOST 6033-80	●	-	●	●	●	●	●
5	pump	right	parallel keyed shaft	●	●	●	●	●	●	●
6	pump	left	parallel keyed shaft	●	●	●	●	●	●	●
7	motor	reverse	splined shaft GOST 6033-80	-	●	-	-	-	-	-
8	pump	right	splined shaft GOST 6033-80	-	●	-	-	-	-	-
9	pump	left	splined shaft GOST 6033-80	-	●	-	-	-	-	-
A	motor	reverse	splined shaft 1 1/2" 23T 16/32DP ANSI B92.1a	-	-	-	-	●	-	-
B	motor	reverse	splined shaft 1 3/8" 21T 16/32DP ANSI B92.1a	-	-	-	-	●	-	-
C	pump	right	splined shaft 22x1,25x9g GOST 6033-80	-	●	-	-	-	-	-
D	pump	left	splined shaft 22x1,25x9g GOST 6033-80	-	●	-	-	-	-	-
E	motor	reverse	splined shaft DIN 5480 ³⁾	-	-	●	●	●	●	-
F	motor	reverse	splined shaft DIN 5480 ⁴⁾	-	-	●	●	●	●	●
G	pump	right	splined shaft DIN 5480 ³⁾	-	-	●	●	●	●	-
H	pump	right	splined shaft DIN 5480 ⁴⁾	-	-	●	●	●	●	●
I	pump	left	splined shaft DIN 5480 ³⁾	-	-	●	●	●	●	-
J	pump	left	splined shaft DIN 5480 ⁴⁾	-	-	●	●	●	●	●
K	motor	reverse	parallel keyed shaft DIN 6885	-	-	-	●	-	-	-
L	pump	right	parallel keyed shaft DIN 6885	-	-	-	●	-	-	-
M	pump	left	parallel keyed shaft DIN 6885	-	-	-	●	-	-	-

F - valves and sensors

code	description	12	28	56	80	112	160	250
0	none	●	●	●	●	●	●	●
1	adjustable pressure-relief valve - left ⁵⁾	●	-	-	-	-	-	-
2	adjustable pressure-relief valve - right ⁵⁾	●	-	-	-	-	-	-
3	non-adjustable pressure-relief valve - left ⁵⁾	●	-	-	-	-	-	-
4	non-adjustable pressure-relief valve - right ⁵⁾	●	-	-	-	-	-	-
5	pressure-relief valves (PRV)	-	-	-	-	-	-	-
6	pressure-relief valves (PRV), flushing valve (FV)	-	-	●	-	-	-	-
7	flushing valve (FV)	-	-	-	●	●	-	-
8	pressure-relief valves (PRV), check valves (CK)	-	-	-	-	-	●	-
9	speed sensor	0	0	-	-	0	-	-
A	pressure-relief valves (PRV), check valves (CK), "OR"-valve (OR), by-pass valve (BP)	-	-	0	-	0	-	-

G - end cap options

code	description	12	28	56	80	112	160	250
0	2 threaded ports at rear side (under 25° to a shaft axis)	●	●	-	-	-	-	-
1	2 threaded ports at rear side (tap in parallel a shaft axis)	●	●	-	-	-	-	-
2	2 threaded ports at rear side (under 50° to a shaft axis)	●	●	-	-	-	-	-
3	2 threaded ports at opposite side, 2 threaded ports at rear side	●	●	●	-	-	-	-
4	1 threaded port at side, 1 flange port at rear side	0	0	-	-	-	-	-
5	1 threaded port at side, 1 threaded port at rear side	●	●	-	-	-	-	-
6	flange ports at rear side	-	-	●	●	●	●	●
7	1 flange port at side, 1 flange port at rear side	-	-	-	-	-	●	●
8	SAE 6000psi 2 flange ports at opposite side (for 310.4.112 - SAE 3000psi)	-	-	●	0	●	-	0
9	2 threaded ports at opposite side	-	-	●	-	-	-	-
A	SAE flange ports at rear side	-	-	-	-	●	-	-
B	SAE 6000psi flange ports at opposite side / flushing valve (FV)	-	-	-	-	●	-	-
C	2 threaded ports at rear side (under 25° to a shaft axis)	●	-	-	-	-	-	-
D	2 threaded ports at opposite side, 2 threaded ports at rear side, M33x2	-	-	●	-	-	-	-

H – shaft seals

code	description	12	28	56	80	112	160	250
B ⁶⁾	NBR	●	●	●	●	●	●	●
F	FKM	●	●	●	●	●	●	●

I - climatic version and category of desposition

code	description	12	28	56	80	112	160	250
Y1 ⁶⁾	temperate climate, placing on open air	●	●	●	●	●	●	●
TB1	tropical climate, placing on open air	●	●	●	●	●	●	●
OM1	maritime climate, placing on open air	●	●	●	●	●	●	●

¹⁾ - omitted in designation of hydraulic units with displacement: 12 cm³ and 28 cm³

²⁾ - not for new project

³⁾ - side fit

⁴⁾ - side fit, smaller size

⁵⁾ - from shaft side view

⁶⁾ - standart program, can be omitted

Technical characteristics.

Fixed displacement axial piston pumps

Size	12	28	56	80	112	160	250
Displacement V_g , ccm/rev	11,6	28	56	80	112	160	250
Shaft speed n, rpm							
- min n_{min}	400	400	400	400	400	400	400
- nom n_{nom}	2400	1920	1800	1500	1200	1200	960
- max n_{max} at input pressure 0.8bar	4000	3000	2500	2240	2000	1750	1500
- peak n_{peak} at input pressure 2bar	6000	4750	3750	3350	3000	2650	2100
Flow Q, l/min							
- min Q_{min}	4,64	11,20	22,40	32,00	44,80	64,00	100,00
- nom Q_{nom}	27,84	53,76	84,00	120,00	134,40	192,00	240,00
- max Q_{max}	46,40	84,00	140,00	179,20	224,00	280,00	375,00
- peak Q_{peak}	69,60	133,00	210,00	268,00	336,00	424,00	525,00
Working pressure P, bar							
- nom P_{nom}	200	200	200	200	200	200	200
- max working P_{max} for pumps 210, 310.3 series	320	320	350	350	350	350	350
- max working P_{max} for pumps 310.4 series	-	-	400	400	400	400	400
Power N, kW							
- nom N_{nom} (at n_{nom} , P_{nom})	15,46	28,00	46,66	59,73	74,66	93,33	125,00
- max N_{max} (at n_{max} , P_{max}) for pumps 210, 310.3 series	24,74	44,80	81,66	104,56	130,66	163,33	218,75
- max N_{max} (at n_{max} , P_{max}) for pumps 310.4 series	-	-	93,33	119,46	149,33	186,66	250,00
Torque T, Nm							
- nom T_{nom} (at P_{nom})	38,86	93,82	187,63	278,58	375,27	536,10	837,65
- max T_{max} (at P_{max}) for pumps 210, 310.3 series	62,19	150,11	328,36	469,08	656,73	938,18	1465,91
- max T_{max} (at P_{max}) for pumps 310.4 series	-	-	375,38	536,10	750,54	1072,20	1675,32
Volume efficiency	0,95	0,95	0,95	0,95	0,95	0,95	0,95
Weight, kg	4	9	17	19	29	45	65

Fixed displacement axial piston motors

Size	12	28	56	80	112	160	250
Displacement V_g , ccm/rev	11,6	28	56	80	112	160	250
Shaft speed n, rpm							
- min n_{min}	50	50	50	50	50	50	50
- nom n_{nom}	2400	1920	1800	1500	1200	1200	960
- max n_{max}	6000	4750	3750	3350	3000	2650	2100
Flow Q, l/min							
- min Q_{min}	0,58	1,40	2,80	4,00	5,60	8,00	12,50
- nom Q_{nom}	27,84	53,76	84,00	120,00	134,40	192,00	240,00
- max Q_{max}	69,60	133,00	210,00	268,00	336,00	424,00	525,00
Input pressure P, bar							
- nom P_{nom}	200	200	200	200	200	200	200
- max working P_{max} for motors 210, 310.3 series	320	320	350	350	350	350	350
- max working P_{max} for motors 310.4 series	-	-	400	400	400	400	400
Power N, kW							
- nom N_{nom} (at n_{nom} , P_{nom})	9,28	17,92	33,60	40,00	44,80	64,00	80,00
- max N_{max} (at n_{max} , P_{max}) for motors 210, 310.3 series	14,84	28,67	58,80	70,00	78,4	112,00	140,00
- max N_{max} (at n_{max} , P_{max}) for motors 310.4 series	-	-	67,20	80,00	89,60	128,00	160,00
Case drain pressure, bar	1	1	2	2	2	2	2
Torque T, Nm							
- nom T_{nom} (at P_{nom})	35	84,6	169,3	241,8	338,7	483,8	756
- max T_{max} (at P_{max}) for motors 210, 310.3 series	56,1	135,5	296,3	423,3	592,7	846,7	1323
- max T_{max} (at P_{max}) for motors 310.4 series	-	-	338,8	483,8	677,4	967,7	1512
Volume efficiency	0,95	0,95	0,95	0,95	0,95	0,95	0,95
Weight, kg	4	9	17	19	29	45	65

Torques shown at Volume efficiency=0.95

All other values - theoretical

Determination of the nominal size range of the pump.

$$\begin{aligned}\text{Flow } Q &= \frac{V_g \cdot n \cdot \eta_v}{1000} && \text{l/min} \\ \text{Torque } T &= \frac{V_g \cdot \Delta P}{20 \cdot \pi \cdot \eta_{mh}} && \text{N}\cdot\text{m} \\ \text{Power } N &= \frac{Q \cdot \Delta P}{612 \cdot \eta_t} && \text{kW}\end{aligned}$$

where:

Q – flow, l/min
 T – torque, N·m
 N – power, kW
 V_g – displacement, ccm/rev
 n – shaft speed, rpm
 ΔP – pressure difference, bar
 η_v – volume efficiency
 η_{mh} – hydraulic mechanical efficiency
 $\eta_t = \eta_v \cdot \eta_{mh}$ – full efficiency coefficient

Determination of the nominal size range of the motor.

$$\begin{aligned}\text{Flow } Q &= \frac{V_g \cdot n}{1000 \cdot \eta_v} && \text{l/min} \\ \text{Torque } T &= \frac{V_g \cdot \Delta P \cdot \eta_{mh}}{20 \cdot \pi} && \text{N}\cdot\text{m} \\ \text{Effective power } N &= \frac{Q \cdot \Delta P \cdot \eta_t}{612} && \text{kW} \\ \text{Shaft speed } n &= \frac{Q \cdot 1000 \cdot \eta_v}{V_g} && \text{rpm}\end{aligned}$$

where:

Q – flow, l/min
 T – torque, N·m
 N – power, kW
 V_g – displacement, ccm/rev
 n – shaft speed, rpm
 ΔP – pressure difference, bar
 η_v – volume efficiency
 η_{mh} – hydraulic mechanical efficiency
 $\eta_t = \eta_v \cdot \eta_{mh}$ – overall efficiency

Requirements for working fluids.

Working fluid temperature:

max constant in hydraulic tank	+85°C
max peak (output from drain hole)	+100°C
min short-term (at cold start)	- 40°C

kinematic viscosity of working fluid:


optimal (constant)	20-35 mm ² /s (cSt)
max starting	1500 mm ² /s (cSt)
min short-term	10 mm ² /s (cSt)

Working fluid fineness:

not lower than class 12 as per GOST 17216-71
 not lower than class 18/15 as per ISO/DIN 4406




210.12.0□.00 - 2 threaded port at rear side (under 25° to a shaft axis)



Technical drawing of a mechanical part, likely a bracket or support, showing a side view with dimensions. The part has a base with two mounting holes and a vertical section with a curved top. Dimensions include a base width of 147.8 and a vertical height of 40.7.




210.12.0□.02 - 2 threaded ports at rear side (under 50° to a shaft axis)



A, B - operating pressure ports

M22x1.5-16, ISO 6149-1


210.12.0□.03 - 2 threaded ports at opposite side, 2 threaded ports at rear side



A, A1, B, B1 - operating pressure ports


M22x1.5-16, ISO 6149-1

210.12.0□.05 - 1 threaded port at side, 1 threaded port at rear side



A - high pressure port M22x1.5-16, ISO 6149-1
S - inlet port M27x2-16, ISO 6149-1


2 threaded ports at rear side, adjustable pressure-relief valve



Hydraulic circuit



2 threaded ports at rear side, non-adjustable pressure-relief valve




Hydraulic circuit




Notes

UNYDROVIA

310.12 Overall dimensions




Shaft ends




End cap options


310.12.00 - 2 threaded ports at rear side (under 25° to a shaft axis)



310.12.01 - 2 threaded ports at rear side (tap in parallel a shaft axis)




310.12.00.02 - 2 threaded ports at rear side (under 50° to a shaft axis)




A, B - operating pressure ports M22x1.5-16, ISO 6149-1

310.12.00.03 - 2 threaded ports at opposite side, 2 threaded ports at rear side



A, A1, B, B1 - operating pressure ports M22x1.5-16, ISO 6149-1

310.12.00.05 - 1 threaded port at side, 1 threaded port at rear side




pump right

pump left

A - high pressure port M22x1.5-16, ISO 6149-1
S - inlet port M27x2-16, ISO 6149-1


2 threaded ports at rear side, adjustable pressure-relief valve



Hydraulic circuit




2 threaded ports at rear side, non-adjustable pressure-relief valve




Hydraulic circuit




310.12.0[.90 - 2 threaded ports at rear side (under 25° to a shaft axis), integrated speed sensor



Connection



310.2.28 Overall dimensions




T - case drain port M18x1,5-18 ISO 6149-1

Shaft ends

Splined shafts


25xf7x1,5x9g GOST 6033-80
ЭВ.25x1,5x16S_{3a} X GOST 6033-51

Parallel keyed shaft



End cap options

310.2.28.0□.00 - 2 threaded ports at rear side (under 25° to a shaft axis)







motor pump right pump left

A, B - operating pressure ports M27x2-24, ISO 6149-1
S - inlet port M33x2-24, ISO 6149-1

310.2.28.0□.01

- 2 threaded ports at rear side (tap in parallel a shaft axis)



motor

A, B - operating pressure ports

S - inlet port

pump right





M27x2-20, ISO 6149-1

M33x2-20, ISO 6149-1

pump left

310.2.28.0□.02

- 2 threaded ports at rear side (under 50° to a shaft axis)



motor

A, B - operating pressure ports

S - inlet port

pump right




M27x2-20, ISO 6149-1

M33x2-20, ISO 6149-1

pump left

310.2.28.0□.03




- 2 threaded ports at opposite side, 2 threaded ports at rear side



A, A1, B, B1 - operating pressure ports M27x2-24, ISO 6149-1

310.2.28.0□.05

- 1 threaded port at side, 1 threaded port at rear side



pump right

A - operating pressure ports


S - inlet port

pump left

M27x2-24, ISO 6149-1

M33x2-24, ISO 6149-1



310.2.28.0□.90 - 2 threaded ports at rear side (under 25° to a shaft axis), integrated speed sensor



Notes

UNYDROVIA


310.3(4).56 Overall dimensions




L = 32 mm for DIN splined shafts, for other splined shafts L = 33,5 mm
T1, T2 - case drain ports M18x1,5-18 ISO 6149-1

Shaft ends


35xf7x2x9g GOST6033




W35x2x30x16x9g DIN5480



W30x2x30x14x9g DIN5480




parallel keyed shaft





End cap options

310.3(4).56.0□.06 - 2 flange at rear side



310.3(4).56.0□.03

- 2 threaded ports at opposite side, 2 threaded ports at rear side





A, A1, B, B1

- operating pressure ports
M27x2-24, ISO 6149-1

310.3(4).56.0□.0D

- 2 threaded ports at opposite side, 2 threaded ports at rear side





A, A1, B, B1


- operating pressure ports
M33x2-24, ISO 6149-1

310.3(4).56.0□.68

- 2 SAE flanges at opposite side, pressure-relief valves, sludging valve






Hydraulic circuit




310.2.28.0□.96


- 2 flanges at rear side, integrated speed sensor



Connection




310.3(4).80 Overall dimensions




Shaft ends


40xf7x2x9g GOST6033





W40x2x30x18x9g DIN5480



W35x2x30x16x9g DIN5480




Parallel keyed shafts





End cap options

310.3(4).80.0[.06 - 2 flange at rear side





310.3(4).80.0□.08

- 2 SAE flanges at opposite sides





310.3(4).80.0□.78

- 2 SAE flanges at opposite side, flushing valve



Hydraulic circuit








310.3(4).112.0□.78




- 2 SAE flanges at opposite side, flushing valve

Hydraulic circuit



310.3(4).112.0□.AA


- 2 SAE flanges at rear side, pressure-relief valves, check valves



S - charge pressure port M14x1.5-14, ISO 6149-1



Y - "OR" valve port M14x1.5-14, ISO 6149-1

Hydraulic circuit




310.3(4).112.0□.96

- 2 flanges at rear side, integrated speed sensor





Connection





45xh8x2x9g GOST6033-80





310.3(4).160.0□.06

- 2 flanges at rear side




310.3(4).160.0□.07

- 1 flange at side, 1 flange at rear side






pump right



pump left


310.3(4).160.0□.8A

- 2 SAE flanges at rear side, pressure-relief valves, check valves




S - charge pressure port M18x1.5-12, ISO 6149-1

Hydraulic circuit



310.3(4).250 Overall dimensions






T1, T2 - case drain ports M22x1,5-18 ISO 6149-1
R - air bleed M14x1,5-15 ISO 6149-1

Shaft ends

50xh8x2x9g ГOCT6033



W50x2x30x24x9g DIN5480

parallel keyed shaft




End cap options


310.3(4).250.0.06 - 2 flange at rear side



motor





pump right




pump left

310.3(4).250.0□.07

- 1 flange at side, 1 flange at rear side



pump right



pump left

310.3(4).250.0□.0A

- 2 SAE flanges at rear side

