



**TECHNICAL DATA.**

**MATERIALS**

End ring and end cap: Zinc plated Steel  
 Inner core: Zinc plated Steel  
 Gasket: NBR 70 Sh. A  $\pm 5$

**FILTER ELEMENT CHARACTERISTIC**

Oil Flow. From: External / To: Internal  
 Filter Media: Fiber 12  $\mu\text{m}$  (c)  $\beta > 1000$  ISO 16889  
 Filter Area: 465  $\text{cm}^2$   
 Collapse Pressure: Min.  $\Delta p$  210 bar (21 MPa)

**TEMPERATURE (ISO 2943)**

Working Temperature. From:  $-25\text{ }^\circ\text{C}$  / To:  $+110\text{ }^\circ\text{C}$

**COMPATIBILITY (ISO 2943)**

Full with fluids: HH-HL-HM-HV-HTG  
 (according to ISO 6743/4)

**PACKING**

Packaging Filter in a single box

APPROVATO  
 ZORZI 27-10-15

(Prodotto)	PLANET FILTERS S.p.A.				Bolgare BG	
(Materiale)	Disegn.	Data	Nome	(Superfici)		
	Contr.	27-10-15	BELOTTI	-		
		27-10-15	ZANELLI	Originale (Denominazione)		
	Tolleranze generali			A3	SHD0060FD21	
	Quote senza indicazione di tolleranza: ISO 2768-mK			N° Disegno	032.0015.3	
	(Peso)	Scala 1.5:1		Rev.	1/1	
	Dis. Grezzo	Sostituito da:		Sostituisce:		