Fastening collars "light line" for SAIP typical accumulators

Ordering code	Description	Dmin [mm]	Dmax [mm]	A	B	C	E	Weight [kg]	WA	L/LAV	LA/LAS	LASS	SI	APV	PAW	AMP
CFOZ57LF120	Fastening collar light line ø54÷58 (W1 60-63) in GALVANIZED CARBON STEEL with base plate, with rubber 124 mm	54	58													
CFOZ60LF120	Fastening collar light line ø60÷63 (W1 64-67) in GALVANIZED CARBON STEEL with base plate, with rubber 124 mm	60	63													
CFOZ64LF120	Fastening collar light line ø62÷66 (W1 68-73) in GALVANIZED CARBON STEEL with base plate, with rubber 124 mm	62	66												PAW 1 (280 barg)	
CFOZ72LF120	Fastening collar light line ø67÷72 (W1 74-79) in GALVANIZED CARBON STEEL with base plate, with rubber 124 mm	67	72	124	81	45	13	0,3	WA 0,16						PAW 0,5-0,75	
CFOZ84LF120	Fastening collar light line ø79÷84(W1 86-91) in GALVANIZED CARBON STEEL with base plate, with rubber 124 mm	79	84													
CFOZ84LF160	Fastening collar light line ø79÷84(W1 86-91) in GALVANIZED CARBON STEEL with base plate, with rubber 144 mm															
CFOZ90LF120	Fastening collar light line ø85÷90 (W1 92-97)in GALVANIZED CARBON STEEL with base plate, with rubber 124 mm	85	90													
CFOZ90LF160	Fastening collar light line ø85÷90 (W1 92-97) in GALVANIZED CARBON STEEL with base plate, with rubber 144 mm															
CFOZ96LF120	Fastening collar light line ø91÷96 (W1 98-103) in GALVANIZED CARBON STEEL with base plate, with rubber 124 mm	91	96	124	81	45	13	0,3	WA 0,35 (100 barg)	LAV 0,5						AMP 0,5
CFOZ96LF160	Fastening collar light line ø91÷96 (W1 98-103) in GALVANIZED CARBON STEEL with base plate, with rubber 144 mm			144	93	45	17	0,5								
CFOZ102LF160	Fastening collar light line ø97÷105 (W1 104-112) in GALVANIZED CARBON STEEL with base plate, with rubber 144 mm	97	105	144	93	45	17	0,5	WA0,35 (250 barg) WA 0,5 (210 barg)	L 0,35				APV 0,5	PAW 3 (250 barg)	
CFOZ111LF160	Fastening collar light line ø106÷114 (W1 113-121) in ACCIAIO AL CARBONIO ZINCATO con piastrina base 144 mm	106	114	144	93	45	17	0,5	WA 0,75 (100 barg)				SI 1-2,5	APV 0,35		
CFOZ120LF160	Fastening collar light line ø115÷123 (W1 122-130) in GALVANIZED CARBON STEEL with base plate, with rubber 144 mm	115	123	144	93	45	17	0,5	WA 0,75 (210, 280 barg) WA 1 (210-280 barg)	LAV 0,75-1,5 APV 2,5	LA 0,75-1-1,5-3	LASS 0,75-1-1,5-3				
CFOZ128LF160	Fastening collar light line ø124÷134 (W1 131-139) in GALVANIZED CARBON STEEL with base plate, with rubber 144 mm	124	134											APV 0,75-1,5-3		
CFOZ137LF160	Fastening collar light line ø133÷141 (W1 140-148)in GALVANIZED CARBON STEEL with base plate, with rubber 144 mm	133	141	144	93	45	17	0,5	WA 0,75 (350 barg)							
CFOZ146LF160	Fastening collar light line ø141÷154 (W1 149-161) in GALVANIZED CARBON STEEL with base plate, with rubber 144 mm	141	154	144	93	45	17	0,5	WA 1,4 (140 -250 barg) WA 2 (140-250 barg)							
CFOZ146LF210	Fastening collar light line ø141÷154 (W1 149-161)in GALVANIZED CARBON STEEL with base plate, with rubber 214 mm			214	145	50	24	0,5								
CFOZ159LF160	Fastening collar light line ø155÷167 (W1 162-174)in GALVANIZED CARBON STEEL with base plate, with rubber 144 mm	155	167	144	93	45	17	0,5	WA 1,4 (350 barg) WA 2 (350 barg)							
CFOZ159LF210	Fastening collar light line ø155÷167 (W1 162-174)in GALVANIZED CARBON STEEL with base plate, with rubber 214 mm			214	145	50	24	0,5								
CFOZ172LF160	Fastening collar light line ø168÷181(W1 175-187) in GALVANIZED CARBON STEEL with base plate, with rubber 144 mm	168	181	144	93	45	17	0,5	WA 3-3,5 (250 barg)		LA 4-6-10-12		SI 4-6-10L			
CFOZ172LF210	Fastening collar light line ø168÷181(W1 175-187) in GALVANIZED CARBON STEEL with base plate, with rubber 214 mm			214	145	50	24	0,5								
CFOZ186LF160	Fastening collar light line ø181÷193 (W1 188-200) in GALVANIZED CARBON STEEL with base plate, with rubber 144 mm	181	193													
CFOZ186LF210	Fastening collar light line ø181÷193 (W1 188-200) in GALVANIZED CARBON STEEL with base plate, with rubber 214 mm															
CFOZ210LF210	Fastening collar light line ø207÷219 (W1 214-226) in GALVANIZED CARBON STEEL with base plate, with rubber 214 mm	207	219													

